



Medidas das presilhas

S-505 TOPpres

Código	Lote mínimo	Peso unitario (Kg)	Diámetro del cable Pol. (in)	Diámetro del cable (mm)	Dimensiones									
					Largo		Ø Externo		Ø Int. Cono		Largo Cono		Ø Interno	
					A		B		D		E		G	
					Pol. (in)	(mm)	Pol. (in)	(mm)	Pol. (in)	(mm)	Pol. (in)	(mm)	Pol. (in)	(mm)
825N	100	0,036	1/4"	6,35	1"	25	0,66	16,80	0,31	7,88	0,28	7,12	0,47	11,90
841N	100	0,052	5/16"	7,93	1,50	38	0,91	23,10	0,44	11,20	0,44	11,20	0,62	15,80
826N	100	0,054	3/8"	9,52	1,50	38	0,91	23,10	0,47	11,90	0,39	9,91	0,66	16,80
827N	100	0,132	1/2"	12,70	2,00	51	1,22	31,00	0,63	16,00	0,56	14,20	0,91	23,10
828N	100	0,259	5/8"	15,87	2,75	70	1,47	37,30	0,75	19,10	0,63	16,00	1,09	27,70
829N	100	0,400	3/4"	19,05	3,19	81	1,72	43,70	0,91	23,10	0,84	21,30	1,28	32,50
830N	50	0,620	7/8"	22,22	3,56	91	2,03	51,50	1,03	26,20	1,00	25,40	1,53	38,90
831N	50	0,890	1"	25,40	4,00	102	2,28	58,00	1,16	29,50	1,13	28,60	1,72	43,70
832N	30	1,180	1.1/8"	28,57	4,81	122	2,50	63,50	1,28	32,50	1,25	31,80	1,94	49,30
833N	30	1,540	1.1/4"	31,75	5,19	132	2,78	70,50	1,44	36,50	1,41	35,80	2,16	55,00
834N	30	1,950	1.3/8"	34,92	5,81	148	3,00	76,00	1,56	39,70	1,56	39,70	2,38	60,50
835N	30	2,260	1.1/2"	38,10	6,25	159	3,25	82,50	1,69	42,90	1,69	42,90	2,63	67,00
836N	30	3,670	1.3/4"	44,45	7,25	184	3,84	97,50	1,94	49,20	1,97	50,00	3,13	79,50
837N	20	5,100	2"	50,80	8,50	216	4,38	111,00	2,25	57,00	2,25	57,00	3,63	92,00
838N	20	10,430	2.1/2"	63,50	10,50	267	5,50	140,00	2,75	70,00	2,81	71,50	4,50	114,00
839N	10	13,340	3"	76,20	12,00	305	6,00	152,00	3,25	82,50	3,38	86,00	5,00	127,00

